

## Kessel

	Stk	cm	cm	lfm	m3	cm	Stk	
Boden ( K B)	2	70	140	1897,5	0,01785	4,5	19	85,5
	2	51	102					
Deckel (K D)	2	71	142	1897,5	0,03195	5	1	5
	2	90	180					
Seitenteil (K R)	2	46	92	1897,5	0,0184	10	6	60
	2	80	160					
Winkel	2	4,5	9	1897,5	0,0184	20	10	200
	2	20	40					
Seitenteil (K R 2)	2	46	92	1897,5	0,0184	25	8	200
	2	80	160					
Winkel A2	3	4,5	13,5	1897,5	0,0184	26	2	52
	4	20	80					
Seitenteil (K S 1 + 2)	4	60	240	1897,5	0,0138	30	2	60
	4	46	184					
Winkel B	4	4,5	18	1897,5	0,0138	36	8	288
	4	25	100					
Trennwand (K T)	2	40	80	1897,5	0,004	40	5	200
	2	20	40					
Winkel B	1	20	20	1897,5	0,1044	41	2	82
	1	5	5					
						0	0	0
						98	3426,5	
						Schnitte	98	49
								3475,5

## Y-Stück

	Stk	cm	cm	lfm	m3
Boden ( Y B)	1	70	70	1529	0,01435
	2	41	82		
	1	40	40		
Deckel ( Y D )	2	61	122	1529	0,02745
	1	90	90		
	1	60	60		
Seitenteil A ( Y R 2)	2	80	160	1529	0,0144
	2	36	72		
Winkel	3	4,5	13,5	1529	0,0144
	4	10	40		
Seitenteil A ( Y R 1)	2	40	80	1529	0,0072
	2	36	72		
Winkel	2	10	20	1529	0,0072
	2	4,5	9		
Seitenteil C	4	50	200	1529	0,009
	4	36	144		
Winkel	4	4,5	18	1529	0,009
	4	25	100		
Trennwand ( Y T)	2	30	60	1529	0,0039
	2	26	52		
Winkel	1	20	20	1529	0,0039
	1	4,5	4,5		

3426,5